

# HIKVISION

لیست قیمت رسمی آبان ماه ۱۴۰۲

تارتن دژ آریانا

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نماینده مرکزی محصولات هایک ویژن

1

2

3

4

5

6

Click for More  
information

DS-2CE16D0T-ITPF(2.8mm)

DS-2CE16D0T-ITPFS

DS-2CE16D0T-ITF(3.6mm)

DS-2CE16D0T-ITFS(2.8)

DS-2CE16D0T-ITFS(3.6mm)

DS-2CE16D0T-EXIF



Price (Rials)

1٠,٤٣٠,٠٠٠

1٤,٣٩٠,٠٠٠

1٤,1٩٠,٠٠٠

1٧,٤٢٠,٠٠٠

1٧,٤1٠,٠٠٠

1٢,٩٨٠,٠٠٠

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

Resolution

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.01Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

0.02Lux/F1.2

Lens

2.8mm Fixed

2.8/3.6/6mm Fixed

2.8/3.6mm Fixed

2.8mm Fixed

3.6mm Fixed

2.8/3.6mm Fixed

Viewing Angle

106.4°

106.4°/79.6° /51.9°

101°/79.6°

106.4°

79.6°

102°/81°

IR Range

Up to 25m

Up to 25m (Exir)

Up to 30m (Exir)

Up to 30m (Exir)

Up to 30m (Exir)

Up to 20m

Body Type

Plastic

Plastic

Metal

Metal

Metal

Metal

IP Standard

IP67

IP67

IP67

IP67

IP67

IP66

OSD Menu

No

No

No

No

No

No

WDR

DWDR

DWDR

DWDR

DWDR

DWDR

DWDR

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, HLC, DNR, BLC,  
2D DNR, SwitchableSmart IR, Switchable, Built  
in micSmart IR, HLC, DNR, BLC,  
2D DNR, SwitchableHLC,2D DNR, BLC,  
Switchable, Built-in  
microphoneHLC,2D DNR, BLC,  
Switchable, Built-in  
microphone

2D DNR, BLC, Switchable

7

8

9

10

11

12

Click for More  
information

DS-2CE16D0T-EX1PF

DS-2CE16D3T-ITF

DS-2CE16D3T-IT3F(2.8mm)

DS-2CE17D0T-IT1F

DS-2CE17D0T-IT3F(2.8mm)

DS-2CE10DF0T-F



Price (Rials)

۱۲,۴۰۰,۰۰۰

۲۱,۶۶۰,۰۰۰

۲۲,۲۴۰,۰۰۰

۱۸,۵۰۰,۰۰۰

۲۳,۱۶۰,۰۰۰

۳۲,۱۳۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

Resolution

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.02Lux/F1.2

0.02Lux/F1.2

0.005Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

0.001Lux/F1.0

Lens

2.8/3.6mm Fixed

2.8/3.6mm Fixed

2.8mm Fixed

2.8/3.6mm Fixed

2.8mm Fixed

2.8/3.6mm Fixed

Viewing Angle

96.5°/76.9°

106°/82°

106°

101°/79.6°

106.4°

98°/76°

IR Range

Up to 20m (Exir)

Up to 30m (Exir)

Up to 50m (Exir)

Up to 30m (Exir)

Up to 40m

Up to 20m

Body Type

Plastic

Metal

Metal

Metal &amp; Plastic

Metal &amp; Plastic

Metal

IP Standard

IP66

IP67

IP67

IP67

IP67

IP67

OSD Menu

No

No

No

No

No

No

WDR

DWDR

Yes (120db)

Yes (120db)

DWDR

DWDR

DWDR

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

2D DNR, BLC, AGC,  
Switchable3D DNR,HLC, BLC,  
Switchable3D DNR,HLC, BLC,  
Switchable3D DNR,HLC, BLC, AGC,  
Switchable

HLC, BLC, AGC, Switchable

HLC, BLC, AGC, Switchable

13

14

15

16

17

18

Click for More  
information

DS-2CE10DF3T-F(3.6mm)

DS-2CE10DF3T-FS(2.8mm)

DS-2CE12DF3T-F(3.6mm)

DS-2CE12DF3T-FS(2.8mm)

DS-2CE76D0T-ITPF(C)(2.8)

DS-2CE76D0T-EXIPF(2.8mm)



Price (Rials)	۲۴,۳۰۰,۰۰۰	۲۴,۰۷۰,۰۰۰	۲۳,۴۷۰,۰۰۰	۲۸,۳۳۰,۰۰۰	۱۲,۳۲۰,۰۰۰	۱۳,۳۹۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Dome	Dome
Imaging Sensor	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel
Resolution	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P	HD1080P
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.0005Lux/F1.0	0.0005Lux/F1.0	0.0005Lux/F1.0	0.0005Lux/F1.0	0.01Lux/F1.2	0.01Lux/F1.2
Lens	3.6mm Fixed	2.8mm Fixed	3.6mm Fixed	2.8mm Fixed	2.8mm Fixed	2.8mm Fixed
Viewing Angle	77°	98°	77°	98°	103°	96.5°
IR Range	Up to 20m (ColorVu)	Up to 20m (ColorVu)	Up to 40m (ColorVu)	Up to 40m (ColorVu)	Up to 20m (Exir)	Up to 20m (Exir)
Body Type	Metal	Metal	Metal	Metal	Plastic	Plastic
IP Standard	IP67	IP67	IP67	IP67	IP66	IP66
OSD Menu	No	No	No	No	No	No
WDR	Yes (130db)	Yes (130db)	Yes (130db)	Yes (130db)	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	HLC, BLC, Smart IR, Switchable, 3D DNR	HLC, BLC, Smart IR, Switchable, 3D DNR, Built in mic	HLC, BLC, Smart IR, Switchable, 3D DNR	HLC, BLC, Smart IR, Switchable, 3D DNR, Built in mic	Smart IR, HLC,BLC, Switchable	Smart IR, HLC,BLC, Switchable

19

20

21

22

23

24

Click for More  
information

DS-2CE76D0T-ITPFS

DS-2CE76D0T-ITMF(2.8)

DS-2CE76D0T-ITMFS(2.8)

DS-2CE76D3T-ITPF

DS-2CE76D3T-ITMF(2.8mm)

DS-2CE56D0T-VFIR3F



Price (Rials)

۱۴,۸۴۰,۰۰۰

۱۶,۴۴۰,۰۰۰

۱۸,۸۱۰,۰۰۰

۱۷,۴۲۰,۰۰۰

۲۳,۸۴۰,۰۰۰

۲۲,۲۴۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

2 Megapixel

Resolution

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

HD1080P

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.01Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

0.005Lux/F1.2

0.005Lux/F1.2

0.01Lux/F1.2

Lens

2.8/3.6/6mm Fixed

2.8mm Fixed

2.8mm Fixed

2.8/3.6/6mm Fixed

2.8mm Fixed

2.8 - 12mm VariFocal

Viewing Angle

106°/79.6°/51°

101°

106.4°

106°/82° /51°

106°

105°/ 32°

IR Range

Up to 20m (Exir)

Up to 30m

Up to 30m (Exir)

Up to 30m(Exir)

Up to 30m(Exir)

Up to 40m

Body Type

Plastic

Metal

Metal

Plastic

Metal

Metal &amp; Plastic

IP Standard

IP66

IP67

IP67

IP66

IP67

IP66

OSD Menu

No

No

No

Yes

No

No

WDR

DWDR

DWDR

DWDR

Yes (120db)

Yes (120db)

DWDR

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, HLC,BLC,  
SwitchableSmart IR, ICR, HLC,BLC, 2D  
DNR, SwitchableICR,AGC, Switchable,  
Built in micSmart IR, HLC,BLC,  
SwitchableSmart IR, HLC,BLC,  
Switchable, 3D DNRSmart IR, ICR, AGC,  
Switchable

25

26

27

28

29

30

Click for More  
information

DS-2CE78D0T-IT3FS

DS-2CE70DF0T-PF

DS-2CE70DF3T-PF(3.6mm)

DS-2CE72DF3T-F(3.6)

DS-2CE16H0T-ITPF

DS-2CE16H0T-ITPFS(2.8)



Price (Rials)	۲۳,۸۴۰,۰۰۰	۲۴,۷۲۰,۰۰۰	۲۶,۹۸۰,۰۰۰	۲۵,۴۱۰,۰۰۰	۱۷,۷۴۰,۰۰۰	۲۰,۷۷۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Bullet	Bullet
Imaging Sensor	2 Megapixel	2 Megapixel	2 Megapixel	2 Megapixel	5 Megapixel	5 Megapixel
Resolution	HD1080P	HD1080P	HD1080P	HD1080P	5MP (2560*1944)	5MP (2592*1944)
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.01Lux/F2.0	0.001Lux/F1.0	0.0005Lux/F1.0	0.0005Lux/F1.0	0.01Lux/F1.2	0.01Lux/F1.2
Lens	2.8/3.6/6mm Fixed	2.8/3.6/6mm Fixed	3.6mm Fixed	3.6mm Fixed	2.8/3.6/6mm Fixed	2.8mm Fixed
Viewing Angle	98°/76°/50°	98°/76°/50°	77°	77°	85.5°/80.1°/57.1°	85.5°
IR Range	Up to 40m (Exir)	Up to 20m (ColorVu)	Up to 20m (ColorVu)	Up to 40m (ColorVu)	Up to 20m (Exir)	Up to 25m (Exir)
Body Type	Plastic	Plastic	Plastic	Metal & Plastic	Plastic	Plastic
IP Standard	IP67	IP66	IP66	IP67	IP67	IP67
OSD Menu	No	No	No	No	No	No
WDR	DWDR	DWDR	Yes (130db)	Yes (130db)	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	AGC, Switchable, Built in Mic	AGC, Switchable	AGC, Switchable, 3D DNR	AGC, Switchable, 3D DNR	Smart IR, BLC,AGC, DNR, Switchable	Smart IR, HLC,BLC,AGC, 2D DNR, Switchable, Built in Mic

31

32

33

34

35

36

Click for More  
information

DS-2CE16H0T-ITPFS(3.6mm)

DS-2CE16H0T-ITF(3.6mm)

DS-2CE16H0T-ITFS

DS-2CE17H0T-IT1F

DS-2CE17H0T-IT3F(2.8mm)

DS-2CE17H0T-IT3F(3.6mm)



Price (Rials)

۲۱,۲۰,۰۰۰

۱۸,۰۰,۰۰۰

۲۳,۰۵,۰۰۰

۲۳,۲۳,۰۰۰

۲۳,۳۰,۰۰۰

۲۴,۱۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

5 Megapixel

Resolution

5MP (2592\*1944)

5MP (2592\*1944)

5MP (2560\*1944)

5MP (2560\*1944)

5MP (2560\*1944)

5MP (2560\*1944)

Signal System

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

HDTVI,AHD,HDCVI,ANLOG

Min. Illustration

0.01Lux/F1.2

0.01Lux/F1

0.01Lux/F1

0.01Lux/F1.2

0.01Lux/F1.2

0.01Lux/F1.2

Lens

2.8/3.6mm Fixed

2.8/3.6mm Fixed

2.8/3.6/6mm Fixed

2.4/2.8/3.6mm Fixed

2.8mm Fixed

3.6mm Fixed

Viewing Angle

85.5°/80.1°

85.5°/80.1°

85.5°/80.1°/57.1°

110°/85°/80°

85°

80°

IR Range

Up to 25m (Exir)

Up to 20m (Exir)

Up to 30m (Exir)

Up to 30m

Up to 40m

Up to 40m

Body Type

Plastic

Metal

Metal

Metal &amp; Plastic

Metal &amp; Plastic

Metal &amp; Plastic

IP Standard

IP67

IP67

IP67

IP67

IP67

IP67

OSD Menu

No

Yes

No

No

No

No

WDR

DWDR

DWDR

DWDR

DWDR

DWDR

DWDR

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, HLC,BLC,AGC, 2D  
DNR, Switchable, Built in  
Mic2D DNR, DWDR,  
Switchable2D DNR, Switchable,  
Built in MicSmart IR, 2D DNR,  
HLC,BLC, SwitchableSmart IR, 2D DNR,  
HLC,BLC, SwitchableSmart IR, 2D DNR,  
HLC,BLC, Switchable

37

38

39

40

41

42

Click for More  
information

DS-2CE17H0T-IT3FS(2.8mm) DS-2CE17H0T-IT5F(3.6mm) DS-2CE12HFT-F(3.6mm) DS-2CE10HFT-F(3.6mm) DS-2CE56H0T-IT1F DS-2CE76H0T-ITPF(2.4mm)



Price (Rials)	۲۹,۷۹۰,۰۰۰	۲۴,۴۶۰,۰۰۰	۴۰,۱۶۰,۰۰۰	۳۴,۸۱۰,۰۰۰	۲۰,۹۰۰,۰۰۰	۱۷,۴۱۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Dome	Dome
Imaging Sensor	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel
Resolution	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.01Lux/F1.2	0.01Lux/F1.2	0.0005Lux/F1.0	0.0005Lux/F1.0	0.01 Lux/F1.2	0.01 Lux/F1.2
Lens	2.8mm Fixed	3.6/6/8mm Fixed	3.6/6mm Fixed	3.6/6mm Fixed	2.8/3.6/6mm Fixed	2.4mm Fixed
Viewing Angle	85°	80°/57°/41°	80.0°/49.3°	80.0°/49.3°	105°/85°/65°	110°
IR Range	Up to 40m	Up to 80m	Up to 40m	Up to 20m	Up to 20m (Exir)	Up to 20m (Exir)
Body Type	Metal & Plastic	Metal & Plastic	Metal	Metal	Metal & Plastic	Plastic
IP Standard	IP67	IP67	IP67	IP67	IP67	IP67
OSD Menu	No	No	No	No	Yes	No
WDR	DWDR	DWDR	Yes (130db)	Yes (130db)	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	Smart IR, 2D DNR, HLC,BLC, Switchable, Built in mic	Smart IR, 2D DNR, HLC,BLC, Switchable	Smart IR, 3D DNR, HLC,BLC,HLS,Anti-banding, Switchable	Smart IR, 3D DNR, HLC,BLC,HLS,Anti-banding, Switchable	Smart IR, ICR, AGC, BLC, Switchable	Smart IR, ICR, AGC, BLC, HLC



43

44

45

46

47

48

Click for More  
information

DS-2CE76H0T-ITPF(2.8mm)

DS-2CE76H0T-ITMF(2.8)

DS-2CE76H0T-ITMFS(2.8)

DS-2CE78H0T-IT1F(2.4mm)

DS-2CE78H0T-IT3F

DS-2CE78H0T-IT3FS(3.6mm)



Price (Rials)	١٦,٣٠٠,٠٠٠	٢١,٤٤٠,٠٠٠	٢٤,٢٩٠,٠٠٠	٢٣,٨٦٠,٠٠٠	٢٥,٧٩٠,٠٠٠	٢٥,٤٤٠,٠٠٠
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel	5 Megapixel
Resolution	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)	5MP (2560*1944)
Signal System	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG	HDTVI,AHD,HDCVI,ANLOG
Min. Illustration	0.01 Lux/F1.2	0.01 Lux/F1.2	0.01 Lux/F1.2	0.01 Lux/F1.2	0.01 Lux/F1.2	0.01 Lux/F2.0
Lens	2.8mm Fixed	2.8mm Fixed	2.8mm Fixed	2.4 mm Fixed	2.8/3.6/6mm Fixed	2.8/3.6/6mm Fixed
Viewing Angle	85°	105°	85°	110°	85°/80°/57°	85.5°/80°/57°
IR Range	Up to 20m (Exir)	Up to 30m (Exir)	Up to 30m	Up to 30m (Exir)	Up to 40m (Exir)	Up to 40m
Body Type	Plastic	Metal	Metal	Metal & Plastic	Metal & Plastic	Metal & Plastic
IP Standard	IP67	IP67	IP67	IP67	IP67	IP67
OSD Menu	No	No	No	No	No	No
WDR	DWDR	DWDR	DWDR	DWDR	DWDR	DWDR
Power Supply	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC	12 VDC
Other Features	Smart IR, ICR, AGC, BLC, HLC	Smart IR, ICR, AGC, BLC, Switchable	Smart IR, ICR, AGC, BLC, Switchable, Built in mic	Smart IR, ICR, AGC, BLC,HLC, Switchable	Smart IR, ICR, AGC,HLC, BLC, Switchable	Smart IR, ICR, AGC, Switchable, Built in mic

49

50

51

52

53

Click for More  
information

DS-2CE79H0T-IT3ZF

DS-2CE72HFT-F28(2.8mm)

DS-2CE72KF0T-FS(2.8mm)

DS-2CE78U8T-IT3

DS-2AE4225TI-D



Price (Rials)

۴۵,۷۸۰,۰۰۰

۴۰,۱۶۰,۰۰۰

۳۷,۴۰۰,۰۰۰

۶۳,۸۷۰,۰۰۰

۱۸۰,۵۲۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

PTZ

Imaging Sensor

5 Megapixel

5 Megapixel

3K

8.29 Megapixel

2 Megapixel

Resolution

5MP (2560\*1944)

5MP (2560\*1944)

3K (2960\*1665)

8MP (3840\*2160)

1920 × 1080

Signal System

HDTVI,AHD,HDCVI,ANLOG

HD-TVI

HD-TVI

HD-TVI

HD-TVI

Min. Illustration

0.01 Lux/F1.6

0.0005 Lux/F1.0

0.001 Lux/F1.0

0.003 Lux/F1.2

0.005 Lux/F1.6

Lens

2.7-13.5mm Motorized

2.8mm Fixed

2.8mm Fixed

2.8/3.6/6mm Fixed

4.8 mm-120mm

Viewing Angle

95°-26°

99.7°

102°

105°/85°/65°

25x Optical Zoom

IR Range

Up to 40m

Up to 20m (ColorVu)

Up to 40m (ColorVu)

Up to 60m (Exir)

Up to 100m

Body Type

Metal

Metal &amp; Plastic

Metal &amp; Plastic

Metal &amp; Plastic

Metal

IP Standard

IP67

IP67

IP67

IP67

IP66

OSD Menu

No

No

No

No

No

WDR

DWDR

Yes (130db)

DWDR

Yes (120db)

Yes (120db)

Power Supply

12 VDC

12 VDC

12 VDC

12 VDC

12 VDC

Other Features

Smart IR, 2D DNR,  
Switchable, AGC

Smart IR, 3D DNR

Smart IR, 3D DNR, Built in  
mic

Smart IR, ICR

Smart IR, ICR, Switchable,  
DarkFighter

54

55

56

57

58

59

Click for More information

DS-7216HGHI-K1

IDS-7204HQHI-M1/S

IDS-7208HQHI-M1/S

DS-7216HQHI-K1

DS-7216HQHI-M1/S

iDS-7216HQHI-M2/S



Price (Rials)

۷۲,۲۷۰,۰۰۰

۴۶,۵۲۰,۰۰۰

۷۳,۳۹۰,۰۰۰

۱۲۱,۸۰۰,۰۰۰

۱۲۴,۰۹۰,۰۰۰

۱۵۴,۴۰۰,۰۰۰

DVR Type

16+2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP4+1 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP8+2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP16+2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP16+2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP16+2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP

Analog Video Input

16 Ch. HDTV/Analog  
Up to 2MP4 Ch. HDTV/Analog  
Up to 4MP8 Ch. HDTV/Analog  
Up to 4MP16 Ch. HDTV/Analog  
Up to 4MP16 Ch. HDTV/Analog  
Up to 4MP16 Ch. HDTV/Analog  
Up to 4MP

IP Video Input

2 Ch. Up to 5MP

1 Ch. Up to 6MP

2 Ch. Up to 6MP

2 Ch. Up to 6MP

2 Ch. Up to 6MP

2 Ch. Up to 6MP

Audio Input/Output

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

Recording

1080P: 15FPS  
720P: 15FPS  
VGA: 25FPS4MP: 15FPS  
3MP: 15FPS  
1080P: 15FPS4MP: 15FPS  
3MP: 15FPS  
1080P: 15FPS4MP: 15FPS  
3MP: 15FPS  
1080P: 15FPS3K: 30FPS  
5MP: 20FPS  
1080P: 30FPS4MP: 15FPS  
3MP: 15FPS  
1080P: 15FPS

Video Output

1 Port HDMI : 1080P  
1 Port VGA1 Port HDMI 1080P  
1 Port VGA,  
1Ch. CVBS1 Port HDMI 1080P  
1 Port VGA,  
1Ch. CVBS1 Port HDMI : 4K  
1 Port VGA  
1Ch. CVBS1 Port HDMI : 4K  
1 Port VGA  
1Ch. CVBS1 Port HDMI 1080P  
1 Port VGA  
1Ch. CVBS

SATA Interface

1 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

2 HDD up to 10TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265/H.265 pro+  
Compression, ONVIF, Deep  
learningH.265/H.265+  
Compression, ONVIF,  
Smart SearchH.265/H.265+  
Compression, ONVIF,  
Smart SearchH.265/H.265+  
Compression, ONVIF,  
VCA, Smart SearchH.265/H.265 pro+  
Compression, ONVIF,  
VCA, Smart SearchH.265/H.265+  
Compression, ONVIF,  
VCA, Smart Search

60

61

62

63

64

65

Click for More  
information

IDS-7232HQHI-K2

IDS-7232HQHI-M2/S

DS-7204HUHI-K1

DS-7204HUHI-K1/P

DS-7204HUHI-M1/S

DS-7208HUHI-M1/S



Price (Rials)

۲۶۷,۳۲۰,۰۰۰

۲۵۲,۰۲۰,۰۰۰

۶۷,۷۲۰,۰۰۰

۶۷,۴۷۰,۰۰۰

۷۴,۷۲۰,۰۰۰

۱۲۴,۶۳۰,۰۰۰

DVR Type

32+2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP32+2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP4 +2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP4 +2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP4 + 2 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP8 + 4 Ch. quadruple Hybrid  
HD-TVI /AHD/ Analog / IP

Analog Video Input

32 Ch. HDTV/Analog  
Up to 4MP32 Ch. HDTV/Analog  
Up to 4MPSupport  
Up to 5MP resolution  
recordingSupport  
Up to 5MP resolution  
recordingSupport  
Up to 5MP resolution  
recordingSupport  
Up to 5MP resolution  
recording

IP Video Input

2 Ch. Up to 6MP

2 Ch. Up to 6MP

2 Ch. Up to 8MP

2 Ch. Up to 8MP

2 Ch. Up to 8MP

4 Ch. Up to 8MP

Audio Input/Output

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

1Ch. In / 1Ch. Out

Recording

4MP: 15FPS  
3MP: 15FPS  
1080P: 15FPS4MP: 15FPS  
3MP: 15FPS  
1080P: 15FPS5MP: 12FPS  
4MP: 15FPS  
3mp: 18FPS5MP: 12FPS  
4MP: 15FPS  
3mp: 18FPS5MP: 12FPS  
4MP: 15FPS  
3mp: 18FPS5MP: 30FPS  
4MP: 30FPS  
3mp: 30FPS

Video Output

1 Port HDMI : 4K  
1 Port VGA  
1Ch. CVBS1 Port HDMI : 4K  
1 Port VGA  
1Ch. CVBS1 Port HDMI : 1080P  
1 Port VGA1 Port HDMI : 1080P  
1 Port VGA  
CVBS: PAL1 Port HDMI : 2K  
1 Port VGA  
CVBS: PAL1 Port HDMI : 4K  
1 Port VGA

SATA Interface

2 HDD up to 10TB

2 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

1 HDD up to 10TB

Network Interface

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265 Pro+/H.265  
Pro/H.265/ Compression,  
VCAH.265/H.265+  
Compression, ONVIF,  
VCA, Smart SearchH.265/H.265+ COMPR  
Alarm In/Out : 4/1  
Onvif, VCAH.265/H.265+ COMPR  
Alarm In/Out : 4/1  
Built-in PoCH.265/H.265+ COMPR  
Alarm In/Out : N/AH.265 Pro+/H.265 Pro,  
Onvif

66

67

68

Click for More  
information

DS-7216HUHI-K2

IDS-7216HUHI-M2/S

DS-7316HUHI-F4/N



Price (Rials)

۲۱۸,۷۳۰,۰۰۰

۲۲۶,۷۵۰,۰۰۰

۴۴۷,۲۷۰,۰۰۰

DVR Type

16+16Ch.quadruple Hybrid  
HD-TVI /AHD/ Analog / IP16+8 Ch.quadruple Hybrid  
HD-TVI /AHD/ Analog / IP16+2 Ch.quadruple Hybrid  
HD-TVI /AHD/ Analog / IP

Analog Video Input

Support  
Up to 5MP resolution  
recordingSupport  
Up to 5MP resolution  
recordingSupport  
Up to 3MP resolution  
recording

IP Video Input

16 Ch. Up to 8MP

8 Ch. Up to 8MP

2 Ch. Up to 8MP

Audio Input/Output

4Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

4Ch. In / 1Ch. Out

Recording

5MP: 20FPS  
4MP: 25FPS  
3mp: 18FPS5MP: 20FPS  
4MP: 25FPS  
3mp: 18FPS3mp: 15FPS  
2mp: 25FPS  
720p: 25FPS

Video Output

1 Port HDMI : 4K  
1 Port VGA  
CVBS: PAL1 Port HDMI : 4K  
1 Port VGA  
CVBS: PAL2 Port HDMI : 4K/1080p  
1 Port VGA  
CVBS: PAL

SATA Interface

2 HDD up to 10TB

2 HDD up to 10TB

4 HDD up to 6TB

Network Interface

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265/H.265+ COMPR  
Alarm In/Out : 16/4H.265/H.265+ COMPR  
Alarm In/Out : N/AH.265/H.265+ COMPR  
Alarm In/Out : N/A

# HIKVISION

لیست قیمت رسمی آبان ماه ۱۴۰۲








تارتن دژ آریانا

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نمایندگی مرکزی محصولات هایک ویژن

	1	2	3	4	5	6
<a href="#">Click for More information</a>	<a href="#">DS-2CD1023G0E-I(2.8mm)</a>	<a href="#">DS-2CD1023G0-IUF</a>	<a href="#">DS-2CD1043G0-I(4mm)</a>	<a href="#">DS-2CD1053G0-I</a>	<a href="#">DS-2CD1057G0-L</a>	<a href="#">DS-2CD1123G0E-I</a>
						
<b>Price (Rials)</b>	۲۶,۹۴۰,۰۰۰	۴۰,۷۷۰,۰۰۰	۳۵,۱۶۰,۰۰۰	۵۱,۹۴۰,۰۰۰	۵۸,۸۲۰,۰۰۰	۲۶,۳۶۰,۰۰۰
<b>Camera Type</b>	Bullet	Bullet	Bullet	Bullet	Bullet	Dome
<b>Imaging Sensor</b>	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS	1/2.8" Prog. CMOS
<b>Resolution</b>	2MP(1920x1080/30FPS)	2MP(1920x1080/30FPS)	4MP(2560x1440/20fps)	4MP(2560x1440/20fps)	5MP (2560 × 1920/20fps)	2MP(1920x1080/30FPS)
<b>Network Standard</b>	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
<b>Min. Illustration</b>	0.01Lux @ F1.2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F2.0	0.001Lux @ F1.0	0.01Lux @ F1.2
<b>Lens</b>	2.8/4 mm Fixed	2.8/4 mm Fixed	4 mm Fixed	2.8 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
<b>Viewing Angle</b>	112.1°/90.2°	112.1°/90.2°	78.7°	98°	95°/76°	114.8°/86°
<b>IR Range</b>	Up to 30m	Up to 30m (EXIR)	Up to 30m	Up to 30m	Up to 30m (Color Vu)	Up to 30m
<b>Body Type &amp; Standard</b>	Plastic / IP67	Metal/Plastic / IP67	Plastic / IP67	Plastic / IP67	Metal / IP67	Plastic / IP67
<b>SD Card Support</b>	No	Yes (Up to 256G)	No	No	Yes (Up to 256G)	No
<b>Microphone Support</b>	No	Yes (Built in MIC)	No	No	No	No
<b>WDR</b>	DWDR	DWDR	DWDR	DWDR	Yes (120db)	DWDR
<b>WIFI</b>	No	No	No	No	No	No
<b>Power Supply</b>	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
<b>Other Features</b>	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, H.265+ COMP

7

8

9

10

11

12

Click for More  
information

DS-2CD1143G0-I

DS-2CD1143G0-IUF

DS-2CD1153G0-I(4mm)

DS-2CD1323G0E-I

DS-2CD1347G0-L

DS-2CD1353G0-I (2.8mm)



Price (Rials)

۴۱,۷۸۰,۰۰۰

۵۵,۹۸۰,۰۰۰

۵۴,۵۴۰,۰۰۰

۲۹,۵۹۰,۰۰۰

۸۱,۶۵۰,۰۰۰

۵۷,۰۰۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

Resolution

4MP(2560x1440/20fps)

4MP(2560x1440/20fps)

5MP(2560x1920/15FPS)

2MP(1920x1080/25FPS)

4MP(2560x1440/20fps)

5MP(2560x1920/20FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.028Lux @ F2

0.01Lux @ F2.0

0.01Lux @ F2.0

0.01Lux @ F2.0

0.001Lux @ F1.0

0.01Lux @ F2.0

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

Viewing Angle

98°/78.7°

98°/78.7°

75.3°

105°/81°

96.5°/75.8°

98.0°

IR Range

Up to 30m

Up to 30m (Color Vu)

Up to 30m

Up to 30m (EXIR)

Up to 30m (Color Vu)

Up to 30m (EXIR)

Body Type &amp; Standard

Plastic / IP67

Plastic / IP67/ IK10

Plastic / IP67/ IK10

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal/Plastic / IP67

SD Card Support

No

Yes (Up to 256 G)

No

No

No

No

Microphone Support

No

Yes (Built in MIC)

No

No

No

No

WDR

DWDR

Yes (120db)

Yes (120db)

DWDR

No

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, ROI, VCA,  
H.265+ COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, ROI, H.265+  
COMP3D DNR, BLC, ROI, H.265+  
COMP3D DNR, BLC, ROI, H.265+  
COMP



13

14

15

16

17

18

Click for More  
information

DS-2CD1357G0-L

DS-2CD2021G1-I (2.8mm)

DS-2CD2023G2-I

DS-2CD2025FHWD-I

DS-2CD2027G2-L (2.8mm)

DS-2CD2043G2-I (2.8mm)



Price (Rials)

۵۸,۷۹۰,۰۰۰

۴۹,۹۸۰,۰۰۰

۶۱,۲۴۰,۰۰۰

۷۰,۰۶۰,۰۰۰

۷۱,۰۴۰,۰۰۰

۶۶,۵۶۰,۰۰۰

Camera Type

Dome

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

Resolution

5MP(2560x1920/20FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

4MP(2560x1440/30fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.001Lux @ F1.0

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.2

0.005Lux @ F1.6

0.005Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

Viewing Angle

95°/76°

111.6°/91.5°

107°/87°

108°/86.4°

107°

103°

IR Range

Up to 30m (Color Vu)

Up to 30m (EXIR)

Up to 40m

Up to 30m

Up to 40m (Color Vu)

Up to 40m

Body Type &amp; Standard

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

No

Yes (Up to 256 G)

No

Yes (Up to 128 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+  
COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP

19

20

21

22

23

24

Click for More  
information

DS-2CD2043G2-IU(2.8mm)

DS-2CD2046G2-I

DS-2CD2047G2-L

DS-2CD2063G2-I

DS-2CD2066G2-I

DS-2CD2083G2-I



Price (Rials)

۷۹,۱۱۰,۰۰۰

۷۲,۳۷۰,۰۰۰

۷۷,۷۳۰,۰۰۰

۷۳,۰۵۰,۰۰۰

۸۰,۲۲۰,۰۰۰

۷۹,۱۹۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/2.4" Prog. CMOS

1/2.4" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

4MP(2560×1440/30fps)

4MP(2688×1520/30fps)

4MP(2560×1440/30fps)

6MP(3200×1800/25fps)

6MP(3200×1800/25fps)

8MP(3840 × 2160/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0005Lux @ F1.0

0.005Lux @ F1.6

0.003Lux @ F1.6

0.005Lux @ F1.6

Lens

2.8 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

103°

103°/83°

112°/95°

105°/78°

105°/78°

107°/87°

IR Range

Up to 40m

Up to 40m

Up to 40m (Color Vu)

Up to 40m

Up to 40m

Up to 40m

Body Type &amp; Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 256 G)

Yes (Up to 512 G)

Yes (Up to 256 G)

Yes (Up to 512 G)

Yes (Up to 512 G)

Yes (Up to 512 G)

Microphone Support

Yes (Built in MIC)

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP

25

26

27

28

29

30

Click for More  
information

DS-2CD2085G1-I

DS-2CD2086G2-I

DS-2CD2087G2-LU (2.8mm)

DS-2CD2123G2-IU

DS-2CD2126G2-ISU(2.8mm)

DS-2CD2143G2-IU



Price (Rials)

117,160,000

101,040,000

156,550,000

62,810,000

81,540,000

66,890,000

Camera Type

Bullet

Bullet

Bullet

Dome

Dome

Dome

Imaging Sensor

1/1.2" Prog. CMOS

1/1.8" Prog. CMOS

1/1.2" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

Resolution

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

8MP(3072×1728/20fps)

4MP(2688 × 1520/25fps)

2MP(1920x1080/25FPS)

4MP(2688 × 1520/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.008Lux @ F1.2

0.003Lux @ F1.6

0.0005Lux @ F1.0

0.005 Lux @ F1.6

0.002 Lux @ F1.4

0.005 Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

Viewing Angle

102°/78°

111°/87°

102°

107°/87°

107°

103°/84°

IR Range

Up to 30m

Up to 40m

Up to 40m (ColorVu)

Up to 30m

Up to 30m

Up to 30m

Body Type &amp; Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67 &amp; IK10

Metal / IP67 &amp; IK10

Metal / IP67 &amp; IK10

SD Card Support

Yes (Up to 128 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Microphone Support

No

No

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

WDR

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP, DarkFighter3D DNR, BLC, HLC, H.265+  
COMP

31

32

33

34

35

36

Click for More  
information

DS-2CD2147G2

DS-2CD2163G2-IU

DS-2CD2166G2-ISU(2.8mm)

DS-2CD2183G2-IU

DS-2CD2185FWD-I

DS-2CD2H25FWD-IZS



Price (Rials)

۸۶,۹۸۰,۰۰۰

۷۱,۹۲۰,۰۰۰

۸۷,۳۹۰,۰۰۰

۷۴,۲۸۰,۰۰۰

۱۰۸,۴۶۰,۰۰۰

۱۳۸,۸۷۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/1.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.4" Prog. CMOS

1/2.8" Prog. CMOS

1/2.5" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

4MP(2688 × 1520/25fps)

6MP(3200 × 1800/25fps)

6MP(3200 × 1800/25fps)

8MP(3840 × 2160/25fps)

8MP(3840 × 2160/25fps)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.0005 Lux @ F1.0

0.005 Lux @ F1.6

0.003 Lux @ F1.6

0.005 Lux @ F1.6

0.01 Lux @ F1.2

0.005Lux @ F1.2

Lens

2.8 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8-12mm Motorized

Viewing Angle

112°

107°/87°

105°/78°

107°/87°

107°/87°

105°~35°

IR Range

Up to 30m (Color Vu)

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Body Type &amp; Standard

Metal / IP67 &amp; IK10

Metal / IP67 &amp; IK10

Metal / IP67 &amp; IK10

Metal / IP67 &amp; IK10

Metal / IP67 &amp; IK10

Metal / IP66/IK10

SD Card Support

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 128G)

Yes (Up to 128 G)

Microphone Support

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

No

Yes (1.ch Audio Input)

WDR

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC,H.265+  
COMP3D DNR, BLC, HLC,H.265+  
COMP3D DNR, BLC, HLC,H.265+  
COMP3D DNR, BLC, HLC,H.265+  
COMP3D DNR, BLC, HLC,H.265+  
COMP3D DNR, BLC, ROI, HLC, H.265+  
COMP, DarkFighter

37

38

39

40

41

42

Click for More  
information

DS-2CD2327G2-L(2.8)

DS-2CD2347G2-L(2.8mm)

DS-2CD2346G2-IU

DS-2CD2347G2-LU(2.8mm)

DS-2CD1T43G2-LIU(4mm)

DS-2CD2T43G2-2I(2.8mm)



Price (Rials)

۸۱,۱۱۰,۰۰۰

۷۸,۹۱۰,۰۰۰

۷۶,۸۲۰,۰۰۰

۸۹,۷۶۰,۰۰۰

۴۸,۰۱۰,۰۰۰

۶۶,۹۷۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Bullet

Bullet

Imaging Sensor

1/2.8" Prog. CMOS

1/1.8" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

4MP(2688 × 1520/25fps)

4MP(2688 × 1520/25fps)

4MP(2688 × 1520/25fps)

4MP (2560x1440/20fps)

4MP(2688x1520/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.0005 Lux @ F1.0

0.0005 Lux @ F1.0

0.003 Lux @ F1.4

0.0005 Lux @ F1.0

0.005Lux @ F1.6

0.005Lux @ F1.6

Lens

2.8 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

4 mm Fixed

2.8 mm Fixed

Viewing Angle

107°

112°

103°/83°

112°

78°

103°

IR Range

Up to 30m

Up to 30m (Color Vu)

Up to 30m

Up to 30m (Color Vu)

Up to 50m (Hybrid Light)

Up to 60m (EXIR)

Body Type &amp; Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Microphone Support

No

No

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

No

WDR

Yes (120db)

Yes (130db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC,H.265+  
COMP3D DNR, BLC, HLC,H.265+  
COMP3D DNR, BLC, HLC,H.265+  
COMP, DarkFighter3D DNR, BLC, HLC,H.265+  
COMP3D DNR, BLC, HLC, ROI, H.265+  
COMP3D DNR, BLC, HLC, ROI, H.265+  
COMP

43

44

45

46

47

48

Click for More  
information

DS-2CD2T43G2-2I(4mm)

DS-2CD2T43G2-4I(4mm)

DS-2CD2T47G-L

DS-2CD2T63G2-4I

DS-2CD2T66G2-4I

DS-2CD2T83G2-4I



Price (Rials)

٤٤,٩٧٠,٠٠٠

٧٢,٣٨٠,٠٠٠

٩٥,٥٨٠,٠٠٠

٨٢,٣٣٠,٠٠٠

٩٤,٢١٠,٠٠٠

٩٣,٩٠٠,٠٠٠

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.4" Prog. CMOS

1/2.5" Prog. CMOS

Resolution

4MP(2688×1520/25fps)

4MP(2688×1520/25fps)

4MP(2688×1520/25fps)

6MP(3200×1800/25fps)

6MP(3200×1800/25fps)

8MP(3840 × 2160/15fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0005Lux @ F1.0

0.005Lux @ F1.6

0.003Lux @ F1.6

0.005Lux @ F1.2

Lens

4 mm Fixed

4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

84°

84°

112°/95°

107°/87°

105°/87°

102°/79°

IR Range

Up to 60m (EXIR)

Up to 80m (EXIR)

Up to 60m (Color Vu)

Up to 80m (EXIR)

Up to 60m (EXIR)

Up to 80m (EXIR)

Body Type &amp; Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, ROI, H.265+  
COMP3D DNR, BLC, HLC, ROI, H.265+  
COMP3D DNR, BLC, HLC, ROI, H.265+  
COMP3D DNR, BLC, ROI, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP, ROI3D DNR, BLC, HLC, H.265+  
COMP, ROI

49

50

51

52

53

54

Click for More  
information

DS-2CD2T85G1-I5

DS-2CD2T85G1-I8

DS-2CD2T86G2-4I

DS-2CD1643G0-IZ

DS-2CD2643G2-IZS

DS-2CD2666G2-IZS



Price (Rials)

۱۲۲,۲۲۰,۰۰۰

۱۳۴,۷۳۰,۰۰۰

۱۲۰,۱۵۰,۰۰۰

۸۱,۳۵۰,۰۰۰

۱۲۴,۷۱۰,۰۰۰

۱۵۲,۶۴۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2" Prog. CMOS

1/2.5" Prog. CMOS

1/1.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.4" Prog. CMOS

Resolution

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/15fps)

8MP(3840 × 2160/25fps)

4MP(2560 × 1440/20fps)

4MP(2688 × 1520/25fps)

6MP(3200×1800/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.008Lux @ F1.2

0.01Lux @ F1.2

0.003Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0035Lux @ F1.4

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

110.7°/87.1°

102°/79°

111°/87°

102°~31°

95.8°~29.2°

106°~35°

IR Range

Up to 50m

Up to 80m

Up to 80m (EXIR)

Up to 50m (EXIR)

Up to 60m

Up to 60m

Body Type &amp; Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67,IK10

Metal / IP67,IK10

SD Card Support

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 512G)

Microphone Support

No

No

No

No

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC,H.265+  
COMP, ROI3D DNR, BLC, HLC,H.265+  
COMP, ROI3D DNR, BLC, HLC,H.265+  
COMP, ROI3D DNR, BLC, ROI, H.265+  
COMP3D DNR, BLC, ROI, H.265+  
COMP3D DNR, BLC,HLC, ROI, H.265+  
COMP-

55

56

57

58

59

60

Click for More  
information

DS-2CD2683G2-IZS

DS-2CD2686G2-IZS

DS-2CD1743G0-IZ

DS-2CD2743G2-IZS

DS-2CD2783G2-IZS

DS-2CD2785G1-IZS



Price (Rials)

۱۴۲,۶۸۰,۰۰۰

۱۸۱,۵۹۰,۰۰۰

۹۱,۳۴۰,۰۰۰

۱۴۹,۰۰۰,۰۰۰

۱۳۹,۷۲۰,۰۰۰

۱۵۰,۳۲۰,۰۰۰

Camera Type

Bullet

Bullet

Dome

Dome

Dome

Dome

Imaging Sensor

1/2.8" Prog. CMOS

1/2" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2" Prog. CMOS

1/2" Prog. CMOS

Resolution

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

4MP (2560x1440/20fps)

4MP (2560x1440/20FPS)

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.008Lux @ F1.2

0.005Lux @ F1.6

0.005Lux @ F1.6

0.008Lux @ F1.2

0.008Lux @ F1.2

Lens

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

108°~30°

112°~46°

91.2°~28.3°

104°~29°

112°~46°

112°~46°

IR Range

Up to 60m

Up to 50m

Up to 30m (EXIR)

Up to 40m

Up to 30m

Up to 30m

Body Type &amp; Standard

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67,IK10

SD Card Support

Yes (Up to512G)

Yes (Up to128G)

Yes (Up to 256G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Microphone Support

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

No

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+  
COMP-3D DNR, BLC, ROI, H.265+  
COMP- DarkFighter

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, H.265+ COMP,  
Deep Learning3D DNR, BLC, ROI, H.265+  
COMP- DarkFighter3D DNR, BLC, ROI, H.265+  
COMP- DarkFighter



Click for More  
information

DS-2CD2443G0-IW(W)



Price (Rials)

۶۲,۴۷۰,۰۰۰

Camera Type

Cube

Imaging Sensor

1/3" Prog. CMOS

Resolution

4MP (2688x1520/25FPS)

Network Standard

ONVIF

Min. Illustration

0.01Lux @ F1.2

Lens

2.8/4 mm Fixed

Viewing Angle

98°/78

IR Range

Up to 10m

Body Type &amp; Standard

Plastic

SD Card Support

Yes (Up to 128G)

Microphone Support

Yes (Built in MIC)

WDR

Yes (120db)

WIFI

No

Power Supply

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+  
COMP, PIR

62

63

64

65

66

67

Click for More  
information

DS-2SE4C225MWG-E

DS-2DE4225IW-DE T5

DS-2SE4C425MWG-E(14f0)

DS-2DE4425IW-DE T5

DS-2DE7A432IW-AEB(T5)

DS-2CD2955FWD-LS



Price (Rials)

۲۸۸,۳۴۰,۰۰۰

۲۱۹,۶۲۰,۰۰۰

۳۲۹,۰۰۰,۰۰۰

۲۵۲,۱۵۰,۰۰۰

۴۲۰,۹۸۰,۰۰۰

۱۰۲,۹۶۰,۰۰۰

Camera Type

PTZ

PTZ

PTZ

PTZ

PTZ

Fisheye

Imaging Sensor

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS(Bullet)  
1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/1.8" Prog. CMOS

1/2.5" Prog. CMOS

Resolution

2MP(1920x1080/60FPS)

2MP(1920x1080/60FPS)

4MP(2560x1440/60FPS)

4MP(2560 × 1440/30FPS)

4MP(2560 × 1440/30FPS)

5MP(2560 × 1920/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.0005Lux/F1.0  
0.005Lux/F1.6

0.005Lux/F1.6

0.0005Lux/F1.0  
0.005Lux/F1.6

0.005Lux/F1.6

0.005Lux/F1.5

0.01Lux/F1.2

Lens

2.8mm (Bullet)  
4.8-120mm Motorized

4.8-120mm Motorized

2.8mm (Bullet)  
4.8-120mm Motorized

4.8-120mm Motorized

5.9-188.8mm Motorized

1.05mm

Viewing Angle

106°(Bullet)  
25x (PTZ)

25x

96.1°(Bullet)  
25x (PTZ)

25x

32x

180°

IR Range

Up to 30m(Bullet)  
Up to 100m

Up to 100m

Up to 30m(Bullet)  
Up to 100m

Up to 100m

Up to 200m

Up to 8 m

Body Type &amp; Standard

Metal/IP66

Metal/IP66

Metal/IP66

Metal/IP66

Metal/IP66, IK10

Metal

SD Card Support

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 128G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12 VDC &amp; POE(802.3at)

12 VDC &amp; POE(802.3at)

12 VDC &amp; POE(802.3at)

12 VDC &amp; POE(802.3at)

24 VAC &amp; Hi-POE

12VDC &amp; POE(802.3at)

Other Features

16x Digital Zoom, H.265+, HLC,  
BLC, 3D DNR16x Digital Zoom, H.265+, HLC,  
BLC, 3D DNR16x Digital Zoom, H.265+, HLC,  
BLC, 3D DNR16x Digital Zoom, H.265+, HLC,  
BLC, 3D DNR16x Digital Zoom, H.265+, HLC,  
BLC, 3D DNR, DarkFighter

3D DNR, H.265+, Anti-flicker

68

69

70

71

72

73

Click for More  
information

DS-7104NI-Q1/M

DS-7108NI-Q1/M

DS-7604NI-K1

DS-7604NI-K1/4P

DS-7608NI-Q1

DS-7608NI-K1



Price (Rials)

۴۲,۳۸۰,۰۰۰

۴۹,۳۸۰,۰۰۰

۶۱,۵۶۰,۰۰۰

۸۲,۷۴۰,۰۰۰

۵۸,۳۰۰,۰۰۰

۶۸,۳۴۰,۰۰۰

NVR Type

4 Ch

8 Ch

4 Ch

4 Ch / 4 POE

8 Ch

8 Ch

Input BandWidth

40Mbps

60Mbps

40Mbps

40Mbps

80Mbps

80Mbps

Output Bandwidth

60Mbps

60Mbps

80Mbps

80Mbps

80Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 4Mp

Upto 4Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 1080p  
1 Port VGA1 Port HDMI : 1080p  
1 Port VGA1 Port HDMI : 4k  
1 Port VGA1 Port HDMI : 4k  
1 Port VGA1 Port HDMI : 4k  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA : 1080P

POE Ports

-

-

-

4 POE Ports

-

-

SATA Interface

1 HDD up to 6TB

1 HDD up to 6TB

1 HDD up to 8TB

1 HDD up to 8TB

2 HDD up to 8TB

1 HDD up to 8TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP  
Alarm I/O 4/1

74

75

76

77

78

79

Click for More  
information

DS-7608NI-K2

DS-7608NI-K1/8P

DS-7616NI-Q2

DS-7716NI-Q4/16P

DS-7616NI-K1

DS-7616NI-K2



Price (Rials)

۷۱,۲۰۰,۰۰۰

۱۲۶,۱۹۰,۰۰۰

۸۹,۸۱۰,۰۰۰

۲۵۵,۱۴۰,۰۰۰

۸۵,۸۰۰,۰۰۰

۸۲,۹۷۰,۰۰۰

NVR Type

8 Ch

8 Ch / 8 POE

16 Ch

16 Ch / 16 POE

16 Ch

16 Ch

Input BandWidth

80Mbps

80Mbps

160Mbps

160Mbps

160Mbps

160Mbps

Output Bandwidth

80Mbps

80Mbps

80Mbps

80Mbps

80Mbps

160Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4k  
1 Port VGA1 Port HDMI : 4k  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4K  
1 Port VGA : 1080P

POE Ports

-

8 POE Ports

-

16 POE Ports

-

-

SATA Interface

1 HDD up to 8TB

1 HDD up to 8TB

2 HDD up to 8TB

4 HDD up to 8TB

1 HDD up to 8TB

2 HDD up to 10TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

1U

1.5U

Standalone 1U

1U

Other Features

H.265+ COMP  
Alarm I/O 4/1H.265+ COMP  
Alarm I/O 4/1

H.265+ COMP

H.265+ COMP  
Alarm I/O 16/4

H.265+ COMP

H.265+ COMP

	80	81	82	83	84	85
<a href="#">Click for More information</a>	<a href="#">DS-7616NI-K2/16P</a>	<a href="#">DS-7716NI-K4</a>	<a href="#">DS-7732NI-K4</a>	<a href="#">DS-7732NI-K4/16P</a>	<a href="#">DS-7732NXI-K4</a>	<a href="#">IDS-7732NXI-I4/8S</a>



<b>Price (Rials)</b>	۱۸۷,۸۶۰,۰۰۰	۱۸۹,۹۷۰,۰۰۰	۲۱۰,۴۵۰,۰۰۰	۲۳۴,۳۱۰,۰۰۰	۲۳۱,۰۹۰,۰۰۰	۷۱۹,۱۶۰,۰۰۰
<b>NVR Type</b>	16 Ch / 16 POE	16 Ch	32 Ch	32 Ch / 16 POE	32 Ch	32 Ch
<b>Input BandWidth</b>	160Mbps	160Mbps	256Mbps	256Mbps	256Mbps	320Mbps
<b>Output Bandwidth</b>	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps	256Mbps
<b>Audio Input/Output</b>	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
<b>Decoding Capacity</b>	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 12Mp	Upto 8Mp
<b>Video Output</b>	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P
<b>POE Ports</b>	16 POE Ports	-	-	16 POE Ports	-	-
<b>SATA Interface</b>	2 HDD up to 10TB	4 HDD up to 10TB	4 HDD up to 8TB	4 HDD up to 8TB	4 HDD up to 10TB	4 HDD up to 10TB
<b>Network Interface</b>	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M
<b>Chassis</b>	1U	1.5 U	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case
<b>Other Features</b>	H.265+ COMPR	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/8 - Esata 1- DeepinMind

	86	87	88	89
<a href="#">Click for More information</a>	<a href="#">DS-9632NI-I8</a>	<a href="#">IDS-9632NXI-I8/4F</a>	<a href="#">DS-9632NXI-I8/S</a>	<a href="#">IDS-9664NXI-I8/S</a>



<b>Price (Rials)</b>	۷۱۰,۰۰۰,۰۰۰	۳,۲۱۳,۸۹۰,۰۰۰	۷۳۹,۰۲۰,۰۰۰	۹۶۸,۶۳۰,۰۰۰
<b>NVR Type</b>	32 Ch	32 Ch	32 Ch	64 Ch
<b>Input BandWidth</b>	320Mbps	320Mbps	320Mbps	320Mbps
<b>Output Bandwidth</b>	256Mbps	256Mbps	256Mbps	256Mbps
<b>Audio Input/Output</b>	1Ch. In/ 2Ch. Out	1Ch. In/ 2Ch. Out	1Ch. In/ 2Ch. Out	1Ch. In/ 2Ch. Out
<b>Decoding Capacity</b>	Upto 12Mp	Upto 12Mp	Upto 12Mp	Upto 12Mp
<b>Video Output</b>	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P	2 Port HDMI : 4K/1080P 2 Port VGA : 1080P	2 Port HDMI : 4K/1080P 2 Port VGA : 1080P	2 Port HDMI : 4K/1080P 1 Port VGA : 1080P
<b>POE Ports</b>	-	-	-	-
<b>SATA Interface</b>	8 HDD up to 10TB	8 HDD up to 10TB	8 HDD up to 10TB	8 HDD up to 10TB
<b>Network Interface</b>	2 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M
<b>Chassis</b>	19" 1.5 Case	2U	2U	2U
<b>Other Features</b>	H.265+ COMPR Alarm I/O 16/4, RAID	H.265+ COMPR Alarm I/O 16/8, RAID, DeepinMind- Esata 1	H.265+ COMPR Alarm I/O 16/8, RAID, DeepinMind- Esata 1	H.265+ COMPR Alarm I/O 16/8, RAID, DeepinMind