



تارتن دژ آریانا
02152605

Tiandy

تارتن دژ آریانا

AK SERIES

1	TC-C320N Spec: I3/E/Y/2.8MM		Metal+Plastic Housing - Up to 1920x1080@30fps ·S+265/H.265/H.264 - Min. illumination Color: 0.04Lux@F2.2 ·Smart IR, IR Range: 30m, ·Built-in Mic ·Operating Conditions -30°~60°, 0~95% RH ·POE ·Support motion detection	IRR 23,000,000
2	TC-C321N Spec: I3/E/Y/2.8MM		Plastic Housing - Up to 1920x1080@30fps ·S+265/H.265/H.264 - Min. illumination Color: 0.04Lux@F2.2 ·Smart IR, IR Range: 30m, Built-in Mic ·Operating Conditions -30°~60°, 0~95% RH ·POE, IP67 ·Support motion detection	IRR 23,000,000

Network Camera - NVR

Spark - Series

3	TC-C32QN Spec: I3/E/Y/2.8mm/V5.0		2MP Fixed IR Bullet Camera - Metal+Plastic Housing - Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.02Lux@F2.0 ·Smart IR, IR Range: 30m ·Built-in Mic · Operating Conditions -30°C~60°C, 0~95% RH ·POE, IP67	IRR 26,000,000
4	TC-C32XN Spec: I3/E/Y/2.8mm/V5.0		2MP Fixed Turret Camera- Metal+Plastic ·Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.02Lux@F2.0 ·Smart IR, IR Range: 30m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -40°C~65°C, 0~95% RH ·POE, IP67	IRR 26,000,000
5	TC-C34QN Spec: I3/E/Y/2.8MM/V5.0		·Metal+Plastic Housing - Up to 2560x1440@20fps ·S+265/H.265/H.264 - Min. illumination Color: 0.02Lux@F1.6 ·Smart IR, IR Range: 30m ·Built-in Mic ·Operating Conditions -30°~60°, 0~95% RH ·POE, IP67	IRR 54,000,000
6	TC-C34QN Spec: I5W/E/Y/2.8MM/V4.2		4MP Fixed Starlight IR Bullet Camera, ·Metal+Plastic Housing ·Up to 2688X1520@25fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.02Lux@F1.6, ·2 Warm lights, 15m ·Smart IR, IR Range: 50m ·Built-in Mic ·Operating Conditions -30°~60°, 0~95% RH ·POE, IP67	IRR 59,800,000
7	TC-C34XN Spec: I3W/E/Y/2.8MM/V4.2		4MP Fixed Starlight IR Turret Camera- ·Metal+Plastic Housing ·Up to 2688X1520@25fps ·S+265/H.265/H.264 - Min. illumination Color: 0.02Lux@F1.6 ·2 Warm lights, 15m, ·Smart IR, IR Range: 30m ·Built-in Mic ·Operating Conditions -30°~60°, 0~95% RH ·Support tripwire and perimeter ·DC12V, POE	IRR 59,800,000
8	TC-C34XN Spec: I3/E/Y/2.8MM/V5.0		4MP Fixed Turret Camera, ·Metal+Plastic Housing ·Up to 2688X1520@25fps ·S+265/H.265/H.264 - Min. illumination Color: 0.02Lux@F1.6 ·2 Warm lights, 15m, ·Smart IR, IR Range: 30m ·Built-in Mic ·Operating Conditions -30°~60°, 0~95% RH ·Support tripwire and perimeter ·DC12V, POE	IRR 54,000,000
9	TC-R3105 SPEC: I/B/P/L/S		5ch PSE NVR - HD Input · S+265/H.265/H.264 video formats · Connectable to the third-party network cameras · Support live view, storage, and playback of the connected camera at up to 6MP resolution HD Output · 1xHDMI and 1xVGA simultaneous outputs · HDMI Video output at up to 4K resolution HD Storage · 1 SATA interface, up to 8TB for 1 HDD · S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission · 1xRJ45 self-adaptive 10/100 Mbps network interface · PoE Port: 4xRJ45 self-adaptive 10/100 Mbps	IRR 46,500,000
10	TC-R3110 SPEC: I/B/P8/L/S		10ch PSE NVR - HD Input · Plug and play · S+265/H.265/S+264/H.264 video formats · Connectable to the third-party network cameras · Up to 10-channel input · 8 PoE ports · Supports live view, storage, and playback of the connected camera at up to 6MP resolution HD Output · 1xHDMI output · HDMI Video output at up to 4K resolution HD Storage · 1 SATA interfaces, up to 8TB for each HDD · S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission · 1xRJ45 self- adaptive 10/100 Mbps network interface · PoE Port: 8xRJ45 self-adaptive 10/100 Mbps network interfaces	IRR 57,000,000

Wifi - Series

11	TC-C32WN spec: I5/Y/WIFI/4MM/V4.0		2MP Fixed IR Wi-Fi Bullet Camera - Metal+Plastic Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.02Lux@F2.0 ·Smart IR, IR Range: 50m ·Operating Conditions -35°C~65°C, 0~95% RH ·Built-in Mic, SD Card Slot, Reset Button ·Support Wi-Fi ·IP67	IRR 45,000,000
12	TC-C32KN spec: I3/Y/WIFI/2.8MM		2MP Fixed IR Wi-Fi Dome Camera - Metal+Plastic Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.02Lux@F2.0 ·Smart IR, IR Range: 30m ·Operating Conditions -35°C~65°C, 0~95% RH ·Built-in Mic, SD Card Slot, Reset Button ·Support Wi-Fi ·IP67, IK10	IRR 45,000,000

Super lite-Lite & Eco - Series

13	TC-C32HN Spec: I3/E/Y/C/2.8mm/V4.1		2MP Fixed IR Turret Camera - Metal+Plastic Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.02Lux@F2.0 ·Smart IR, IR Range: 30m ·Built-in Mic ·Support tripwire and perimeter ·Operating Conditions -30°C~60°C, 0~95% RH ·POE, DC12V ·IP66	IRR 31,000,000
----	--	---	---	----------------

14	TC-C32WS Spec:I5/E/Y/M/4mm/V4.0		2MP Fixed Starlight IR Bullet Camera - Metal+Plastic Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 50m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Audio I/O 1/1, Alarm I/O 1/1 ·Operating Conditions -35°C~65°C, 0~95% RH ·POE, IP67	IRR 50,000,000
15	TC-C32GS spec: I5/E/Y/C/SD/2.8MM/V4.2		2MP Fixed Starlight IR Bullet Camera, ·Metal+Plastic Housing ·Up to 1920 ×1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6, ·Smart IR, IR Range: 50m ·Built-In Mic ·Support tripwire and perimeter ·Operating Conditions -30°C~60°C, 0~95% RH ·POE, IP67	IRR 55,900,000
16	TC-C32HS I3/E/Y/C/SD/2.8MM/V4.2		2MP Fixed Starlight IR Turret Camera, ·Metal+Plastic Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6, ·Smart IR, IR Range: 30m ·Built-In Mic ·Support tripwire and perimeter ·Operating Conditions -30°C~60°C, 0~95% RH ·POE, IP66	IRR 55,900,000
17	TC-C34GS I5/E/Y/C/SD/2.8MM/V4.2		4MP Fixed Starlight IR Bullet Camera, ·Metal+Plastic Housing ·Up to 2560×1440@25fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6, ·Smart IR, IR Range: 50m ·Built-In Mic ·Support tripwire and perimeter ·Operating Conditions -30°C~60°C, 0~95% RH ·POE, IP67	IRR 64,000,000
18	TC-C34HS Spec: I3/E/Y/C/SD/2.8MM/V4.2		4MP Fixed Starlight IR Turret Camera, ·Metal+Plastic Housing ·Up to 2560×1440@25fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6, ·Smart IR, IR Range: 30m ·Built-In Mic ·Support tripwire and perimeter ·Operating Conditions -30°C~60°C, 0~95% RH ·POE, IP66	IRR 64,000,000
19	TC-C35WS Spec:I5/E/Y/M/2.8mm/V4.0		5MP Fixed Starlight IR Bullet Camera - Full Metal Housing ·Up to 2592x1944@20fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6 ·120dB WDR ·Smart IR, IR Range: 50m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -40°C~60°C, 0~95% RH ·POE, IP67	IRR 87,500,000
20	TC-C35XS Spec:I3/E/Y/C/H/2.8MM		5MP Starlight Mini IP Turret ·Up to 2592x1944@20fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6 Plastic ·120dB WDR ·Smart IR, IR Range: 30m, IP66, Built-in Micro SD card slot, up to 512GB ·Operating Conditions -40°C~60°C, 0~95% RH ·POE	IRR 88,000,000
21	TC-C35KS Spec:I3/E/Y/2.8mm/V4.0		5MP Fixed Starlight IR Dome Camera ·Metal+Plastic Housing ·Up to 2592x1944@20fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6 ·120dB WDR ·Smart IR, IR Range: 30m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -40°C~60°C, 0~95% RH ·POE, IP67, IK10	IRR 82,000,000
22	TC-C35KS Spec:I3/E/Y/M/H/2.8mm/V4.0		·Full Metal Housing ·Up to 2592x1944@30fps, 1920x1080@60fps ·S+265/H.265/H.264/M-JPEG Min. illumination Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 30m ·Support Video Analytics ·Support Human/Vehicle Classification ·Support Face Capture Mode ·Built-in Mic, audio I/O 1/1, alarm I/O 1/1 ·Plug-in Free Operating Conditions -40°C~65°C, 0~95% RH ·POE, IP67, IK10	IRR 129,000,000
23	TC-C38WS Spec:I5/E/Y/M/2.8mm(4mm)/V4.0		8MP Fixed Starlight IR Bullet Camera ·Full Metal Housing ·Up to 3840x2160@20fps ·S+265/H.265/H.264, ·Min. illumination Color: 0.003Lux@F1.6, ·120dB WDR ·Smart IR, IR Range: 50m, Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -40 ~65 °C, 0~95% RH, ·POE, IP67	IRR 128,000,000
24	TC-C38XS Spec: I3/E/Y/M/2.8mm/V4.0		8MP Fixed Starlight IR Turret Camera ·Full Metal Housing ·Up to 3840x2160@20fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.003Lux@F1.6 ·120dB WDR ·Smart IR, IR Range: 30m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -40°C~65°C, 0~95% RH ·POE, IP67	IRR 112,000,000
25	TC-C38KS SPEC: I3/E/Y/2.8mm/V4.0		8MP Fixed Starlight IR Dome Camera ·Metal+Plastic Housing ·Up to 3840x2160@20fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.003Lux@F1.6 ·120dB WDR ·Smart IR, IR Range: 30m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -35°~65°, 0~95% RH ·POE, IP67, IK10	IRR 109,000,000
Color Maker Series				
26	TC-C32XP Spec:W/E/Y/2.8mm/V4.1		2MP Fixed Color Maker Turret Camera ·Metal+Plastic Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 30m ·2 Warm lights, 15m ·Support tripwire and perimeter ·Built-in Mic, support max 512G Micro SD Card ·Operating Conditions -40°C~65°C, 0~95% RH ·POE, DC12V ·IP66	IRR 45,000,000
27	TC-C32XP Spec:I3W/E/Y/2.8mm/V4.2		2MP Fixed Color Maker Turret Camera ·Metal+Plastic Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 30m ·2 Warm lights, 30m ·Support tripwire and perimeter ·Built-in Mic, support max 512G Micro SD Card ·Operating Conditions -40°C~65°C, 0~95% RH ·POE, DC12V ·IP66	IRR 49,500,000
28	TC-C32WP Spec:I5W/E/Y/M/2.8mm/V4.2		·Default: Plastic, M: Metal Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.0008Lux@F1.6 ·2 Warm lights, 15~20m ·Smart IR, IR Range: 50m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -35°C~60°C, 0~95%RH ·POE, IP67	IRR 63,000,000
29	TC-C34XS I3W/E/Y/2.8MM/V4.2		4MP Fixed Color Maker Turret Camera ·Metal+plastic housing Up to 4MP, 2592×1520@25fps S+265/H.265/H.264/H.264M/H.264H Color:0.002Lux@F1.6, AGC ON, B/W:0Lux with IR range up to 30m Built-in Mic Support microSD/microSDHC/microSDXC card, up to 512GB Operating conditions -40°C~65°C, ≤95%RH DC12V±25%, Max. 6W, PoE:IEEE 802.3af, Max. 7W IP66	IRR 49,500,000

30	TC-C34UP W/E/Y/M/4MM/V4.0		4MP Fixed Color Maker Bullet Camera - Full Metal Housing ·Up to 2560x1440@25fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.0002Lux@F1.0 ·120dB WDR ·4 Warmlights, 20~30m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -40°C~60°C, 0~95% RH ·POE, IP67	IRR 105,000,000
Motorized Series				
31	TC-C35US Spec: I8/A/E/Y/M/C/H/2.7-13.5MM		5MP Motorized Starlight IR Bullet Camera - Full Metal Housing ·Motorized Lens 2.7-13.5mm ·Up to 2592x1944@20fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 80m ·Support tripwire and perimeter ·Built-in Mic, support max 512G Micro SD Card ·Audio I/O 1/1, Alarm I/O 1/1 ·Operating Conditions -35°C~65°C, 0~95% RH ·DC12V, POE ·IP67, IK10	IRR 135,000,000
32	TC-C35MS Spec: I3/A/E/Y/M/C/H/2.7-13.5mm/V4.0		5MP Motorized Starlight IR Dome Camera - Full Metal Housing ·Motorized Lens 2.7-13.5mm ·Up to 2592x1944@20fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 30m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button ·Audio I/O 1/1, Alarm I/O 1/1 ·Operating Conditions -35°C~60°C, 0~95% RH ·POE, IP66, IK10	IRR 129,500,000
33	TC-C38MS Spec: I5/A/E/Y/M/H/2.7-13.5/V4.0		·Full Metal Housing ·Motorized Lens 2.7-13.5mm ·Up to 3840x2160@30fps ·S+265/H.265/H.264/M-JPEG ·Min. illumination Color: 0.003Lux@F1.6 ·Smart IR, IR Range: 50m ·Support Video Analytics ·Support Human/Vehicle Classification ·Built-in Mic, audio I/O 1/1, alarm I/O 2/1 ·Plugin Free ·Operating Conditions -35°C~65°C, 0~95% RH ·POE, IP67, IK10	IRR 240,000,000
SPEED DOM - Series				
34	TC-H324S Spec: 25X/I/E/V3.0		2MP 25x Starlight IR PTZ Camera ·Up to 1920X1080@30fps ·Min. illumination Color: 0.001Lux@F1.5 ·Optical zoom: 25x, digital zoom 16x ·Support Human/Vehicle Classification ·Smart IR, IR Range: 150m ·S+265/H.265/H.264/M-JPEG ·Plugin Free ·IP66	IRR 400,000,000
35	TC-H326S Spec: 33X/I/E+/A/V3.0		2MP 33x Starlight IR POE AI PTZ Camera ·Up to 1920X1080@30fps ·Min. illumination Color: 0.001Lux@F1.5 ·Optical zoom: 33x, digital zoom 16x ·Smart IR, IR Range: 200m ·S+265/H.265/H.264/M-JPEG ·Intelligent monitoring/ Face Capture mode ·Support Human/Vehicle Classification ·Support Auto-tracking ·Plugin Free ·IP66	IRR 635,000,000
36	TC-H356S Spec: 30X/I/E+/A/V3.0		5MP 30x Starlight IR POE AI PTZ Camera ·Support Auto-tracking ·Up to 2880x1620@30fps ·Min. illumination Color: 0.001Lux@F1.5 ·Optical zoom: 30x, digital zoom 16x ·Smart IR, IR Range: 200m ·S+265/H.265/H.264/M-JPEG ·Intelligent monitoring/ Face Capture mode ·Support Human/Vehicle Classification ·Plugin Free ·IP66	IRR 850,000,000
NVR - Series				
37	TC-R3105 I/B/I/EU		1 HDD 5ch NVR ·HD Input ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Support live view, storage, and playback of the connected camera at up to 6MP resolution HD Output ·HDMI and VGA simultaneous output ·HDMI Video output at up to 4K (3840x2160) resolution HD Storage ·1 SATA interface, up to 8TB for 1 HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100 Mbps network interface	IRR 39,000,000
38	TC-R3105 SPEC: I/B/P/L		1 HDD 5ch PSE NVR ·HD Input ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Support live view, storage, and playback of the connected camera at up to 6MP resolution HD Output ·1xHDMI and 1xVGA simultaneous outputs ·HDMI Video output at up to 4K resolution HD Storage ·1 SATA interface, up to 8TB for 1 HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100 Mbps network interface ·PoE Port: 4xRJ45 self-adaptive 10/100 Mbps network interfaces	IRR 54,500,000
39	TC-R3108 Spec: I/B/V2.0		1 HDD 8ch NVR ·HD Input ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Support live view, storage, and playback of the connected camera at up to 6MP resolution HD Output ·1xHDMI and 1xVGA simultaneous outputs ·HDMI Video output at up to 4K resolution HD Storage ·1 SATA interface, up to 8TB for 1 HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100 Mbps network interface	IRR 44,000,000
40	TC-R3110 SPEC: I/B/V3.0		1HDD 10ch NVR ·HD Input ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Up to 10-channel input ·Supports live view, storage, and playback of the connected camera at up to 6MP resolution HD Output ·HDMI and VGA simultaneous output ·HDMI Video output at up to 4K (3840x2160) resolution HD Storage ·1 SATA interface, up to 10TB for 1 HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100 Mbps network interface	IRR 72,000,000
41	TC-R3220 Spec: I/B/K/V3.1		2HDD 20ch NVR ·HD Input ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Up to 20-channel input ·Supports live view, storage, and playback of the connected camera at up to 8MP resolution HD Output ·HDMI and VGA simultaneous output ·HDMI Video output at up to 4K (3840x2160) resolution HD Storage ·2 SATA interfaces, up to 10TB for each HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100 Mbps network interface	IRR 207,000,000
42	TC-R3220 Spec: I/B/P16/K/V3.0		2HDD 20ch PSE NVR ·HD Input ·Plug and play ·S+265/H.265/H.264 video formats ·Connectable to the third-party network cameras ·Up to 20-channel input ·16 PoE ports ·Supports live view, storage, and playback of the connected camera at up to 8MP resolution HD Output ·1xHDMI and 1xVGA simultaneous outputs ·HDMI Video output at up to 4K (3840x2160) resolution HD Storage ·2 SATA interfaces, up to 10TB for each HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100/1000 Mbps network interface ·PoE Port: 16xRJ45 self-adaptive 10/100 Mbps network interfaces	IRR 240,000,000
43	TC-R3432 Spec: I/B/K/V3.1		4HDD 32ch NVR ·HD Input ·S+265/H.265/S+264/H.264 video formats ·Connectable to the third-party network cameras ·Support live view, storage, and playback of the connected camera at up to 8MP resolution HD Output ·1xHDMI and 1xVGA simultaneous outputs ·HDMI Video output at up to 4K resolution HD Storage ·1 SATA interface, up to 10TB for 1 HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·1xRJ45 self-adaptive 10/100 Mbps network interface ·PoE Port: 8xRJ45 self-adaptive 10/100 Mbps network interfaces	IRR 290,000,000
44	TC-R3440 Spec: I/B/N/V4.0		4HDD 40ch NVR ·HD Input ·S+265/H.265/S+264/H.264 video formats ·Connectable to the third-party network cameras ·Support live view, storage, and playback of the connected camera at up to 16MP resolution HD Output ·1xHDMI and 1xVGA independent outputs ·HDMI Video output at up to 4K resolution HD Storage ·4 SATA interface, up to 10TB for 1 HDD ·S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission ·2xRJ45 self-adaptive 10/100/1000 Mbps network interface	IRR 510,000,000

45	TC-R3840 Spec:I/B/N		8HDD 40ch NVR - HD Input • S+265/H.265/S+264/H.264 video formats • Connectable to the third-party network cameras • Support live view, storage, and playback of the connected camera at up to 16MP resolution HD Output • HDMI and VGA independent outputs • HDMI Video output at up to 4K resolution HD Storage • 8 SATA interface, up to 18TB for 1 HDD • S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission • 2×RJ45 self-adaptive 10/100/1000 Mbps network interface	IRR 680,000,000
46	TC-R3880 Spec:I/B/N/V4.0		8HDD 80ch NVR - HD Input • S+265/H.265/S+264/H.264 video formats • Connectable to the third-party network cameras • Support live view, storage, and playback of the connected camera at up to 16MP resolution HD Output • HDMI and VGA independent outputs • HDMI Video output at up to 4K resolution HD Storage • 8 SATA interface, up to 18TB for 1 HDD • S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission • 2×RJ45 self-adaptive 10/100/1000 Mbps network interface	IRR 830,000,000

tiandy-cctv.com | 02152605

تهران، خیابان سه‌رودی، کوچه سرمد، پلاک ۱